



PAGING SERVER

Make: PROCOM

Model: PPS-101



DESCRIPTION

The ProPage IP Model PPS-101 is a IP based paging server designed for use with virtually all IP based telephone systems. The unit provides multiple zones / Sub zones there of and all call paging. This ProPage IP unit can drive up to 100 nodes PPS-101 can form the foundation of most paging projects.

SPECIFICATION

Physical:

• 1U 19" Rack Mount

Power:

- Power consumption 350W 5Amps max
- External: 220V 240V

Networking:

- 10/1000 Mbps Ethernet port
- Manual or Dynamic Host Configuration
- Protocol (DHCP) IP address setup.

Protocols:


- SIP
- IAX
- H.323

Environment:

- Temperature: 0 to +40° C
- Humidity: 0 to 85% non-precipitating







FEATURES

- → Announce live or Play back Recorded
- → 50 Station nodes
- → Create & Announce multiple zones / sub zones
- → Easily Connect Loudspeaker System To Existing Computer Networks
- → Compatible With Cisco, Nortel, Avaya, Iwatsu And Most IP Telephone Systems
- → Up gradation possible with HTTP Or local file
- → Protocols supply SIP,IAX2,H.323
- → Schedule play back record
- → Dual Gigabit Ethernet port
- → Network Supervision
- → SIP And Multicast
- → Feedback Eliminator
- → Easy of user interface
- → DHCP